#34 – DESCRIPTION		RL	SN	K	FF
N. Diamond a/e, Blue Model #1687-8, S/N 0034-93 60° — top #IV 151.2 grams before holes.		W 1	.** •		0
Bridge 15.1 w/finish — 17.9 w/retainer. Braces: 1 — 9.3 heavy 6 — 2.9 heavy 2 — 3.3 7 — 5.3 3 — 5.3 8 — 3.3 4 — 2.9 heavy 9 — 9.3 heavy = 44.9 5 — 3.2 Bridge brace 3.5, width .25	50′′				*
Rim 84.1 medium The neck was installed with .037" shims at the nut. 3	3/30/76				
#34-4	- - - -			5 8	:5
6/9/76 Installed on guitar. Saddle relieved.	.25 .50 1.0	.017/.016 .033/.032 .069/.069	.010/.009 .021/.018 .042/.037	.064	~93
#34-3					E.
4/4/76 Top only with bridge, braces and bridge brace. Since the numbers were all too stiff the #1 set was changed to a set having the same dimensions but weighting 8.4 grams instead of 9.3 grams.	.25 .50 1.0	.014/.013 .027/.027 .055/.056	.009/.009 .019/.018 .039/.037	.059	3
An impressive difference for less than a gram each.	<				
#34-2 (and/or -1) 4/3/76			- 1 2		
Top only with bridge, braces and bridge brace. The #1 brace set was replaced and the inboard ones were cut down as needed.	.25 .50 1.0	.013/.013 .026/.025 .051/.052	.008/.008 .016/.016 .034/.031	.054	å il
	S7//		EE 25		- «
	(3) 2 (4)	- 7 - 7			U
					25

TECHNICIAN TECHNICIAN DATE 7-13-76 DESCRIPTION_ GUITAR NUMBER _____ 0034 db 186 +15 Noise +10 1171 +5 519 0 -5 -10 -15-20-25Hz 30. REF 1174.7 1318.5 130.8 146.8 164.8 261.6 293.7 587.3 2349.3 4698.6 523.3 659.3 98. 110. 2637. 4186. 1568. 1760. 2093. 3136. 3520. Ωш C E D O A ပ O A ပ