Ovation®

2758LX

Model Specifications

Bowl Paint Color	Black Textured
Brace Pattern	LX Series Scalloped X
Fingerboard Radius	10”
Inlay Material & Pattern	Inlay - Dot, Polyester MOP #1 Alante
Neck Construction	5 Piece
Neck Finish	Satin Urethane
Neck Reinforcement	Tension Rod - ANS Dual Acting
Neck Shape	Ovation LX Soft V Shape
Neck To Body Joint Location	14th Fret
Neck Width At Nut	1 7/8”
Peg head Angle	10 Degree
Pre-amp	OP-PRO Preamp Assembly w/ 1/4” Jack
Rosette / Epaulets	Epaulette Assembly, Cutaway
Scale Length	25 1/4”
Top Material & Grade	Spruce Bookset “A” Grade
Truss Rod Adjustment Location	Headstock



Ovation®

2758LX

Service Parts Reference

A	**Neck Assembly**	2758LX-X-700	Standard Elite 12-String LX Neck Assembly, deep contour
1	**Machine Heads**	850340-X-15	Machine Head Set - Chrome w/ Ovation Logo 12 String
2	**Truss Rod Cover**	910294-X	Truss Rod Cover - Rosewood
3	**String Nut**	930061-X	String Nut - Tusq - 6 String
4	**Fret Set**	1858-X-690B	22 Standard Notched Fret Set, Elite 12-String
B	**Top & Bowl Assembly**	2758LX-X-200	Standard Elite 12-String Top & Bowl Assembly, deep contour
5	**Strap Knob**	950072-X-17	Strap Lock - Dual Design, Gold
6	**Rosette / Epaulets**	800580-X	Epaulette Assembly, Cutaway
7	**Pre-amp Receptacle**	708922-X-CAN	OP-PRO 1/4" Jack Can
8	**Pre-amp**	708922-X	OP-PRO Preamp Assembly w/ 1/4" Jack
9	**Bridge**	811831-X	Short - Rosewood, No Slot 12 String
10	**Pickup Assy/ Saddle Only**	704600-X 700714-X-19	Saddle One-Piece A/E Classic
	Battery Cover	N/A	N/A
	Shim	930070-X	Shim - OCP-6 Pickup, 1.00mm
	Neck Bolt, Neck Heel	547601-X-00	Screw, Cap - 1/4-20 X 1-5/16
	Neck Bolt, Upper Neck Support Block	547602-X-00	Screw, Cap - 1/4-20 X 3/4

